



Cassette Fan Coil		FP-34	FP-51	FP-68	FP-85	FP-102	FP-136	FP-170	FP-204	FP-238
Cooling Ca. (kw) (Water in 7°C)	H	1.98	2.98	3.68	4.98	5.58	7.2	9.9	10.8	12.6
	M	1.63	2.27	2.81	3.75	4.32	5.53	7.51	8.08	9.68
	L	1.04	1.51	1.89	2.51	2.85	5.53	5	5.55	6.45
Heating Ca. (kw) (Water in 60°C)	H	2.98	4.8	5.48	7.2	8.18	10.8	14.5	16.2	18.9
	M	2.45	3.67	4.19	5.42	6.33	8.17	11	12.35	14.52
	L	1.57	2.44	2.82	3.6	4.52	5.47	7.33	8.48	9.68
Air flow (m³/h)	H	340	510	680	850	1020	1360	1700	2040	2380
	M	280	390	520	640	790	1030	1290	1500	1800
	L	180	260	350	430	520	690	860	1030	1200
Power Input (W)		34	50	58	72	92	126	128	152	198
Current (A)		0.151	0.225	0.258	0.32	0.385	0.561	0.547	0.677	0.882
Noise d B (A)		34	35	37	39	40	41	41	43	44
Static pressure (Pa)		12								
Power Supply		220-240v/ 1ph/50Hz								
Control way		Wired or remote controller								
Water flow (m³/h)		0.42	0.52	0.62	0.86	0.98	1.08	1.58	1.78	1.92
Water pressure drop(kPa)		14	14	16	18	22	25	39	44	46
Water pipe for in/out		ZG3/4"								

 Website: <https://mangoheatpumpcn.en.alibaba.com>
<https://www.mangoenergyheatpump.com>

 E-mail: miranda@mgheatpump.com

Phone/Whatsapp/Wechat: +86-13710428754